



3rd Gen ITEMS Street-Rod

Part#	Description	RACER NET each	
BASIC SYSTEM			
03-BAS4SR	3rd Gen; Basic System with FOUR (4) Std. Shocks, Controller, Programmer, 5-position Remote Switch and all cables.	\$7,600.00	
COMPONENTS of Basic System			
			Qty Total
52xx-yy	SHOCK, 3rd Gen, 48mm bore, 9/16" rod with 1/2"ID Brgs, (Ex: 5243-20: "xx" is 4.3" stroke, "yy" is #20 damping range)	\$1,200.00	4 4,800.00
0304B	CONTROLLER, Oval-Track & Road-Race, 3rd Gen, for 1-4 shocks, 12v	\$1,000.00	1 1,000.00
0209-2SHK	CABLE, SHOCK	\$125.00	4 500.00
0209-2PWR	CABLE, POWER	\$75.00	1 75.00
0304C	PROGRAMMER (Driver I/O Module), 3rd Gen, for 1-4 shocks, 12v	\$775.00	1 775.00
0209-2CHI	CABLE, COMM-HIGH, Programmer box to Controller box	\$125.00	1 125.00
0209-2CLO	CABLE, COMM-LOW, Programmer box to Controller box	\$125.00	1 125.00
0209-2REM-5	CABLE, REMOTE with 5-position Rotary Switch with small box (for mounting on dash etc.)	\$200.00	1 200.00
			Complete System
			7,600.00
OPTIONALS			
0209-2REM-2	CABLE, REMOTE with 2-position Switch (for mounting on steering wheel etc.), (allows access to any 2 of the 5 SETUPS)	\$200.00	
0207-2R2T	Switch w/knob ONLY, Remote, 2-Position, bat handle for Steering Wheel	\$37.50	
0207-2R5R	Switch w/knob ONLY, Remote, 5-Position, rotary with knob - dash mount	\$75.00	
52xx-yyR	Remote RESERVOIR add-on to cost ("R" suffix on Part No.)	\$250.00	
ACCESSORIES			
02-COxyy	Coil-over kits: 2-1/4 or 2-1/2" ID springs, with Jam-nuts (xx: 23=2-1/4" ID, 25=2.50", y: F=flat seat, c=cone seat)	\$62.50	4 250.00

Shock Examples:

Part No.	Description	Mountings	Extended	Comp.	Stroke
5239-20	Fronts	Eye/Eye (bush. OR)	14.74	10.83	3.91
5243-20	Front, JAG Rear & Rear of radically lowered cars	Eye/Eye (bush. OR)	15.51	11.23	4.28
5252-20	Front & Rear	Eye/Eye (bush. OR)	17.32	12.12	5.20
5261-20	Rears	Eye/Eye (bush. OR)	19.35	13.24	6.11
5280-20	Rears	Eye/Eye (bush. OR)	23.18	15.23	7.95
5239-15SB	Front of lowered GMs & big Ford type susp.	stud/barpin	14.21	10.30	3.91
5243-15SB	Front of STD-HEIGHT GMs & big Ford type susp.	stud/barpin	14.98	10.70	4.28
5243-15SD	Front of STD-HEIGHT early Mustang/AMC type susp.	stud/dual-stud	14.76	10.48	4.28
5261-20BE	Rear of lowered/racing most GMs (Monte Carlo etc) susp.	bar-pin/eye	19.35	13.24	6.11
5261-20BS	Rear of lowered/racing 70-82 Camaro susp.	bar-pin/stud	18.82	12.71	6.11
5261-20SE	Rear of lowered/racing 67-69 Camaro, big Ford susp.	stud/eye	18.82	12.71	6.11
5261-20SS	Rear of lowered/racing early Mustang etc. susps.	stud/stud	18.29	12.18	6.11
5280-20BE	Rear of STD-HEIGHT most GMs (Monte Carlo etc) susps.	stud/eye	23.18	15.23	7.95
5280-20SE	Rear of STD-HEIGHT 67-69 Camaro, big Ford susp.	stud/eye	22.65	14.70	7.95

Standard damping ranges are -20, which has a Max damping around 325 lb @ 6 in/sec piston velocity
 The -13 has a Max around 600 lb, -10 around 800 lb & -07 around 1400 lb @ 6 in/sec piston velocity
 Other CUSTOM ranges are available.

MagneShock 5412 new Peachtree Rd. Atlanta GA 30341
 Tel. 770-451-8694 fax 866-586-8854 www.MagneShocks.com
 Dick Anderson CEO dick@magneshocks.com